

ECORASTER® Bloxx 0.5 - specs

Paved areas with less efforts - permeable!



recommended for: - parking spaces
- barrier-free areas
- markers and boundaries

Bloxx 0.5 module	
Dimensions:	18 x 33 x 5 cm 7.09 x 12.99 x 1.97 "
Weight per piece:	0.54 kg 1.19 lbs
Interlock:	notched connectors
Loadability:	up to 800 t/m ² *
Compressive strength:	up to 20 t point axle load (DIN 1072)
Dimensional stability:	-50° / 90° C -58° / 194° F
UV-resistant and weatherproof:	according to DIN EN ISO 4892-2 and DIN EN 60068-2-5
Material:	LDPE, recycled
Tensile strength:	> 5 kN/m
Environmental compatibility:	environmentally neutral according to OECD 202:2004
Highly durable:	according to DIN EN 124:2011 (D400)

* refers to ECORASTER® Bloxx 0.5 module incl. cobblestones

Concrete blocks	
Dimensions:	14.2 x 14.2 x 4.5 cm 5.59 x 5.59 x 1.77 "
Weight per piece:	2.12 kg 4.67 lbs
Dimension, tensile strenght & breaking load:	according to DIN EN 1338; 2003-08
Available colours:	light grey (standard), red, white, anthracite; more colours upon request

Package	concrete blocks	Bloxx 0.5 module
Packaging:	wooden pallet	plastic pallet
Qty. of concrete blocks per pallet:	432	-
Qty. of ECORASTER® Bloxx 0.5 module per pallet:	-	360
Weight per pallet:	940 kg 2 072.35 lbs	205 kg 451.99 lbs
Dimensions cm inch:	120 x 80 x 60 47.24 x 31.5 x 23.6	105 x 135 x 110 41.3 x 53.15 x 43.3
Pallets per truck:	20	22
Qty. per truck:	8 440	7 920

Your contact:



NOTE:

- a. Please note the installation instructions on our website! Subject to change without prior notice. E. & O.E.
- b. The listed details are nominal dimensions and subject to a certain tolerance due to material changes